



Acrycoat is an acrylic based roof paint which can be used on various roof types and exterior waterproofing applications,

Properties

- Excellent water and UV resistance
- Remains flexible to facilitate movement
- Excellent adhesion to a variety of roof types
- Withstands variation in temperature
- Has a long durability

Coverage: The coverage achieved can vary between 4 - 8m/L depending on the porosity and type of substrate. The paint is normally applied in a 2 coat application.

Colours: Available in all standard roof colours

Safety: Non-toxic and non-flammable

Packaging: Supplied in 5L and 20L

HANDLING AND STORAGE

Handling : Keep containers tightly sealed.
Wash hands before eating

Storage : Store in cool well ventilated area
between 5°C and 30°C

EXPOSURE CONTROL/PERSONAL PROTECTION

Engineering measures : Provide good ventilation when
handling large quantities

Personal protection equipment

Respiratory : In case of insufficient ventilation
use suitable respiratory
protection

Eyes : Avoid direct eye contact

Ingestion : Observe the rules of hygiene.
Wash hands before eating

Skin : Wear protective gloves. Remove
soiled or soaked clothing
immediately

MATERIAL SAFETY DATA

COMPOSITION

Resin base : Acrylic emulsion

HAZARDOUS IDENTIFICATION

Physical/chemical hazards : Non-toxic and non-flammable

Human health hazards

Respiratory : May cause irritation

Eyes : May cause irritation

Skin : No irritation

Ingestion : May cause gastro-intestine
irritation

FIRST AID MEASURES

Inhalation : Move to area where there is
fresh air

Eyes : Rinse eyes with clean water for
10 mins

Seek medical attention if symptoms persist

Ingestion : Do not induce vomiting. Seek
medical attention

Skin : Wash hands with soap and
water. Remove contaminated
clothing

FIRE-FIGHTING MEASURES

- Paint is non-flammable but the dry residue is combustible.
- Expect no direct explosion hazard.
- Use CO₂, dry powder or foam.

ACCIDENTAL RELEASE MEASURES

Personal precautions : Surface may be slippery

Spill : Contain and collect spillage.

Dispose of according to local regulations.
Do not allow spillage to enter sewerage drains.

PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Coloured viscous liquid

Odour : Characteristic PVAc

Density : ± 1.10g/cm³

Solid content : ± 50%

STABILITY AND REACTIVITY

Stability : Stable under recommended
conditions

Conditions to avoid : Excessive heat. Store between
5°C and 30°C

Material to avoid : Oxidising agents, strong alkaline
and acidic materials

TOXICOLOGICAL INFORMATION

- Prolonged and frequent skin contact may cause irritation
- Prolonged inhalation may lead to headaches and nausea

ECOLOGICAL INFORMATION

There is no data available on the preparation itself

DISPOSAL INSTRUCTIONS

- Do not allow to enter drains or waterways
- Dispose of in accordance to local applicable legislation
- Empty containers are suitable for recycling

TRANSPORT INFORMATION

Not classified as dangerous for transport

REGULATORY INFORMATION

Classification : Non-hazardous

S2 : Keep out of reach of children



Date of Issue: February 2021. Version 2. The information in this document is based on the present state of our knowledge and on current national laws. The product is not to be used for purposes other than those specified. It is always the responsibility of the user to take all necessary steps in order to fulfill the demands laid down in the local rules and legislation. The information contained in this document is meant as a description of the safety requirements of this product, it is not to be considered as a guarantee of the product's properties.